


Material Safety Data Sheet



Sodium Hydroxide, Pellets

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Sodium Hydroxide, Pellets

OTHER/GENERIC NAMES: Caustic soda bead, dry, granular or solid; Caustic soda; Lye

PRODUCT USE: Industrial

MANUFACTURER: Reheis Inc.
235 Snyder Avenue
Berkeley Heights, NJ 07922

FOR MORE INFORMATION CALL: 908-464-1500
(Monday-Friday, 9:00am-4:30pm)

IN CASE OF EMERGENCY CALL: 800-424-9300
(24 Hours/Day, 7 Days/Week) (CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>WEIGHT %</u>
Sodium hydroxide	1310-73-2	>97
Sodium carbonate	497-19-8	<3

Trace impurities and additional material names not listed above may appear in Section 15 of this MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

OSHA Hazard Communication Standard: *This product is considered hazardous under the OSHA Hazard Communication Standard.*

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: White, odorless pellets. Causes burns to skin and eyes. Harmful if inhaled or swallowed. Corrosive. Hygroscopic.

POTENTIAL HEALTH HAZARDS

SKIN: Severe and rapid corrosion from contact. Extent of damage depends on duration of contact. Even dilute solutions exert a destructive effect, following prolonged contact. Mist from solutions is extremely corrosive.

EYES: Contact rapidly causes severe damage. Permanent corneal damage almost inevitably results. Even dilute solutions may produce similar effects, although less rapidly. Mist from solutions is extremely corrosive.

INHALATION: Inhalation of mist or dust can injure the entire respiratory tract with painful and corrosive action on tissue. Irritancy expected to become noticeable at 2 mg/m³ in air. The effects of inhalation can vary, depending upon extent of exposure, from mild mucous membrane irritation to sudden, severe bronchopneumonia.



MATERIAL SAFETY DATA SHEET

Sodium Hydroxide, Pellets

INGESTION: Severe and rapid corrosive burns of the mouth, gullet and gastrointestinal tract will result, if swallowed. Effects include severe pain, difficulty in breathing, vomiting, diarrhea and collapse. Some effects may be delayed. Estimated average fatal dose is 5 g (human, adult).

DELAYED EFFECTS: None known.

Ingredients found on one of the three OSHA designated carcinogen lists are listed below.

<u>INGREDIENT NAME</u>	<u>NTP STATUS</u>	<u>IARC STATUS</u>	<u>OSHA LIST</u>
No ingredients listed in this section.			

4. FIRST AID MEASURES

SKIN: Immediately flush under a safety shower. If wearing goggles, flush head and face thoroughly before removing goggles. Next, wash victim's hands until all chemical is removed. Then remove contaminated clothing and shoes. Contact a physician. Continue washing for one to two hours and then move to a medical facility if a physician is not available (but only after at least one hour of showering).

EYES: Immediately flush with large amounts of water for at least 15 minutes, holding eyelids apart to facilitate irrigation. Speed is essential. Call a physician. If none is available, irrigate another 15-30 minutes before moving patient to a medical facility. Have an ophthalmologist make an evaluation of eye injury.

INHALATION: Remove to fresh air (to be handled by protected personnel). If breathing is difficult, or if victim is cyanotic (blue skin) give oxygen provided a qualified operator is present. Get medical attention.

INGESTION: Do not induce vomiting. If possible, and if conscious, immediately give large amounts of water or milk. This may be followed by dilute vinegar or fruit juice to neutralize alkali. Get medical attention.

ADVICE TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT:	Not flammable.
FLASH POINT METHOD:	Not applicable.
AUTOIGNITION TEMPERATURE:	Not applicable.
UPPER FLAME LIMIT (volume % in air):	Not applicable.
LOWER FLAME LIMIT (volume % in air):	Not applicable.
FLAME PROPAGATION RATE (solids):	Not applicable.
OSHA FLAMMABILITY CLASS:	Not flammable.

EXTINGUISHING MEDIA:

If involved in a fire, flood with water, taking care not to splash or scatter this material, and keeping it away from common metals. Avoid carbon dioxide because it reacts exothermically with this material.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Will react with metals such as aluminum, tin, and zinc (and alloys of these materials) to generate hydrogen gas, a fire and explosive hazard. Some material may vaporize in a fire. Contact with water or moisture may generate sufficient heat to ignite combustible materials.



MATERIAL SAFETY DATA SHEET

Sodium Hydroxide, Pellets

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus and full protective clothing, including eye protection and boots, to protect against vaporized material and mist. Material can melt in a fire and molten material can react violently with small amounts of water (spattering or misting), and with certain common metals to liberate flammable hydrogen gas.

6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR OTHER RELEASE: (See section 8 for recommended personal protective equipment.)

Clean-up personnel need protection against inhalation and/or skin and eye contact hazards. Dry product can be promptly shoveled up for recovery or disposal. CAUTION! Avoid dusting and skin or eye contact. Also, delay in clean-up may allow absorption of moisture from the atmosphere, increasing clean-up difficulties. Control the disposal of the waste solid. Flush contaminated surfaces with water and neutralize with dilute acid (preferably acetic acid) to remove final traces. (Sodium bicarbonate may also be used to partially neutralize.) Finally, rinse with water; attempt to keep out of sewer. Any release to the environment of this product may be subject to federal and/or state reporting requirements. Check with appropriate agencies.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

7. HANDLING AND STORAGE

NORMAL HANDLING: (See section 8 for recommended personal protective equipment.)

Do not get in eyes, on skin or on clothing. Avoid breathing dust or mist, if generated. Keep container closed when not in use. Use with adequate ventilation and wash thoroughly after handling. When making solutions, use sufficient agitation and cooling, while adding slowly to surface of solution, to avoid splattering. Avoid handling conditions that may lead to spills, leaks, ejections, or to the formation of dust or mist. Wear protective clothing.

STORAGE RECOMMENDATIONS:

Store in closed containers in a dry, well-ventilated area separate from acids, peroxides, metals, easily ignitable materials and other incompatibles. Protect against moisture and water. Protect against physical damage. Drains for storage or use areas for this material should have retention basins for pH adjustment and dilution of spills and flushings before discharge.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Not necessary for pellets. However, if made into a solution or if ground up and mist or dust is generated, provide local exhaust ventilation. In the absence of dust or mist, natural ventilation is adequate. Ventilation facilities should be of corrosion-resistant construction.

In the event hydrogen gas is generated, a severe ventilation problem is rapidly introduced. Smothering CO₂, coupled with good local ventilation or respiratory protection, is probably the best emergency action. In this situation, ventilation facility must be explosion-resistant if such an emergency is likely to happen.



MATERIAL SAFETY DATA SHEET

Sodium Hydroxide, Pellets

PERSONAL PROTECTIVE EQUIPMENT

- SKIN PROTECTION:** Wear neoprene or rubber gloves and full protective clothing (apron, boots, etc.) if there is any possibility of contact with pellets, dust or liquid or mist from solutions. Contaminated clothing should be removed promptly and washed before reuse.
- EYE PROTECTION:** Wear chemical safety goggles if there is any possibility of contact with liquid or mist with the eyes. Add a face shield if there is any possibility of contact with liquid with the face. Do not wear contact lenses if handling liquid or dusty solid material.
- RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.
- ADDITIONAL RECOMMENDATIONS:** A safety shower and eye wash fountain should be readily available. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

EXPOSURE GUIDELINES

<u>INGREDIENT NAME</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT</u>
Sodium hydroxide	2 mg/m ³ ceiling	2 mg/m ³ TWA	-----

¹ = Limit established by Reheis Inc.

² = Workplace Environmental Exposure Level (AIHA).

³ = Biological Exposure Index (ACGIH).

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	White pellets; hygroscopic.
PHYSICAL STATE:	Solid
MOLECULAR WEIGHT:	40.00
CHEMICAL FORMULA:	NaOH
ODOR:	Odorless
SPECIFIC GRAVITY (water = 1.0):	2.13 @ 25C
SOLUBILITY IN WATER (weight %):	29.6 @ 0C
pH:	14 (5% solution)
BOILING POINT:	1390C
MELTING POINT:	318C
VAPOR PRESSURE:	Negligible; 1 mm Hg @ 739C
VAPOR DENSITY (air = 1.0):	Not applicable
EVAPORATION RATE:	Negligible
% VOLATILES:	Negligible
FLASH POINT:	Not flammable

COMPARED TO:



MATERIAL SAFETY DATA SHEET

Sodium Hydroxide, Pellets

(Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

Stable under normal conditions. Rapidly absorbs carbon dioxide and moisture from the air.

INCOMPATIBILITIES:

Common metals and their alloys; acids and their anhydrides; easily oxidizable compounds, including explosives, aldehydes and unsaturated organics; nitrocarbons and chlorocarbons. Strong exothermic reaction with water or moisture (generates much heat).

HAZARDOUS DECOMPOSITION PRODUCTS:

None known.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

IMMEDIATE (ACUTE) EFFECTS:

LD₅₀ (ipr, mouse): 40 mg/kg
Rabbit skin: 500 mg / 24 hr / severe
Rabbit eye: 50 µg / 24 hr / severe

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Data not available.

OTHER DATA:

None.

12. ECOLOGICAL INFORMATION

Aquatic toxicity: 125 ppm / 96 hr / mosquito fish / TLm / fresh water
180 ppm / 23 hr / oysters / lethal / salt water

13. DISPOSAL CONSIDERATIONS

RCRA

Is the unused product a RCRA hazardous waste if discarded? Yes If yes, the RCRA ID number is: D002



MATERIAL SAFETY DATA SHEET

Sodium Hydroxide, Pellets

OTHER DISPOSAL CONSIDERATIONS:

Waste Sodium Hydroxide Pellets may be handled by first reducing to an aqueous solution by adding water with care, neutralizing as per Spill procedures and flushed to sewer with lots of water (regulations permitting) or disposed through a licensed contractor. Since disposal may be subject to federal, state or local regulations (EPA corrosive waste, aqueous form), users should review their operations in terms of applicable federal, state and local laws and regulations, then consult with appropriate regulatory agencies before discharging or disposing of waste material.

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

US DOT HAZARD CLASS: 8, PG II
US DOT ID NUMBER: UN1823
PROPER SHIPPING NAME: Sodium hydroxide, solid

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Listed on the TSCA inventory.

OTHER TSCA ISSUES: None

SARA TITLE III/CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

<u>INGREDIENT NAME</u>	<u>SARA/CERCLA RQ (lb)</u>	<u>SARA EHS TPQ (lb)</u>
Sodium hydroxide	1000	-----

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: Immediate

SARA 313 TOXIC CHEMICALS:

The following ingredients are SARA 313 "Toxic Chemicals" and may be subject to annual reporting requirements. CAS numbers and weight percents are found in Section 2.

<u>INGREDIENT NAME</u>	<u>COMMENT</u>
No ingredients listed in this section.	



MATERIAL SAFETY DATA SHEET

Sodium Hydroxide, Pellets

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

<u>INGREDIENT NAME</u>	<u>WEIGHT %</u>	<u>COMMENT</u>
No ingredients listed in this section.		

ADDITIONAL REGULATORY INFORMATION:

None

WHMIS CLASSIFICATION (CANADA):

Class E

FOREIGN CHEMICAL CONTROL INVENTORY STATUS:

All components listed on Canada(DSL); Europe(EINECS); Australia (AICS); Japan (ENCS); Korea (ECL); Philippines (PICCS); China (IECSC).

16. OTHER INFORMATION

CURRENT ISSUE DATE: March 1, 2005

PREVIOUS ISSUE DATE: May, 2002

CHANGES TO MSDS FROM PREVIOUS ISSUE DATE ARE DUE TO THE FOLLOWING:

Changes to sections 1, 8, 15 and 16.

OTHER INFORMATION: HMIS: 3-0-2
NFPA: 3-0-2

All information, statements, data, advice and/or recommendations, including, without limitation, those relating to storage, loading/unloading, piping and transportation (collectively referred to herein as "information") are believed to be accurate and reliable. However, no representation or warranty, express or implied, is made as to its completeness, accuracy, fitness or a particular purpose or any other matter, including, without limitation, that the practice or application of any such information is free of patent infringement or other intellectual property misappropriation. Reheis Inc. is not engaged in the business of providing technical, operational, engineering or safety information for a fee, and therefore, any such information provided herein has been furnished as an accommodation and without charge. All information provided herein is intended for use by persons having requisite knowledge, skill and experience in the chemical industry. Reheis Inc. shall not be responsible or liable for the use, application or implementation of the information, provided herein, and all such information is to be used at the risk, and in the sole judgement and discretion, of such persons, their employees, advisors and agents.